



March | 2025 AUS

ReidTM Lifting Plate

Compliance Document

ReidTM Lifting Plate
SLP comply with
AS 3850.1:2024


Reid™ Lifting Plate



Reid Lifting Plates are typically used in instances where a lifting anchor has been overlooked or missing. It must be used where the load direction is aligned with the cleat and minimal side load is applied.



Figure 1:
Reid™ Lifting Plate



Reid™ Lifting Plate Key Features:













- Designed for use where a lifting anchor has been omitted or installed incorrectly in a concrete panel.
- Suitable for use with thicknesses of 150mm and above.
- 5 tonne WLL
- Manufactured in accordance with AS 3850.1:2024
- Made in Australia
- NATA Proof Load Certificate

5LP



Compliance Details

Table I: AS 3850.1:2024 Compliance Details

Clause number	Requirement	Compliant
2.2	The Working Load Limit has been determined by testing in accordance with Appendix A, using a FOS per Table 2.1.	
2.6	WLL determined in accordance with clause 2.2.	
	Manufactured from ductile materials.	
	When loaded to ultimate failure, failure shall occur in a ductile manner away from any weld zones, with evidence of distortion and plastic deformation and all fracture faces shall exhibit ductile failure mechanisms.	
	Each clutch shall be proof-tested, certified and uniquely identified.	
	Each clutch shall be permanently marked with a unique identifier (traceable to the proof tests), the manufacturers symbol or name and the WLL or compatible anchor identifier.	
A3	Testing and recording of results.	
A4	Statistical evaluation of test results, using formula A4, $X_k = x(1 - k_s \text{COV})$.	
A5	Production Validation through testing to confirm compliance of critical specification requirements (dimensions, material properties and load bearing capacity where appropriate).	
A8	During design validation, clutches shall be tensile tested to determine R_u .	
	Each clutch shall be proof tested in accordance with clause 2.6.	
	Tensile testing shall be in accordance with A8.2.3.	



Reid™ Lifting Plate comply with **AS 3850.1:2024** Compliant




Product Specification

AS 3850.1:2024
Compliant



Reid Lifting Plates are typically used in instances where a lifting anchor has been overlooked or missing.

The Reid Lifting Plate must be used where the load direction is aligned with the cleat and minimal side load is applied.



The Reid Lifting Plate requires 4x BraceSet™ anchors

(Product Code: BA20115) for installation into concrete.



Go to www.reid.com.au for a copy of the BraceSet AS 3850.1:2024 compliance document.


The Reid Lifting Plate is marked with its rated Working Load Limit – 5T.

The Working Load Limit of 5t @20 MPa (when positioned away from an edge) and when the lift design is certified by the Reid™ Engineering department.


Please note:

- The Working Load Limit is for use in face lift type in-plane lifts where the plate has minimal side loads.
- 5LP is required to be proof loaded on an annual basis.

Product Specification - Dimensions Of 5LP




Product Specification - 5LP Cleat Position and Load Direction




Plane A

Lifting plate can be loaded in 180 degrees in the main direction



Plane B

but can only have ± 30 degrees from vertical in the sideways direction.



TESTED
TO LOCAL
CONDITIONS



Installation

(with post-installation QA check)


Table 2: Lifting Plate Product Code

Product Code	Description	Capacity
5LP	5 tonne Reid Lifting Plates	5 Tonne

Please note:

Requires 4x BraceSet™ anchors (Product Code: BA20115) installed as per the BraceSet Technical Data Sheet

Product Specification - Minimum edge distances



Please note:

It is critical that there is 300mm minimum edge distances for the 5LP.


Installation Specification

Anchor	Part No.	Drill Hole Diameter (mm)	Hole Depth (mm)	Set up Torque (Nm)	Min. Edge Distance (mm)	Min. Distance to Another Plate (mm)	Min. Concrete Strength (MPa)
BraceSet	BA20115	20	114	150	300	750*	>20**

*750mm or as specified by ramsetreid™ engineer.

**Ensure that the minimum concrete strength achieved is more than 20MPa

1. Centralize the 5LP at proposed lifting point with lifting eye parallel to lifting direction, with specified minimum distances from concrete edge and another plate.



2. Drill one hole for each corner with nominated diameter and depth.

3. Blow/Vacuum dust from the hole.

4. Position and drive the anchor with mash hammer into hole until it makes contact with the lifting plate.

5. Tighten the anchor bolts with a calibrated torque wrench to the nominated assembly torque*.

*Use calibrated torque wrench only, in accordance with AS 3850.1:2024, clause 5.1.2.

Note: If reinforcing is struck and the required depth cannot be achieved, please follow the Aborted Hole Process on page 6.



Aborted Hole Process:

If reinforcing is struck and the required depth cannot be achieved, the following process shall be followed:

Case 1 – for Mistake Plate subject to rotation experiencing multi-directional shear (e.g. rotation of precast panels)

1. Aborted hole must be filled with high strength grout/mortar. Grout/mortar strength should be equivalent or greater than concrete strength at time of lift.
2. Mistake Plate shall be relocated 100mm in any direction from original position (maintaining the minimum edge distances) and redrill the holes.

Case 2 – for Mistake Plate subject to one direction shear (e.g. tilt-up panels being lifted with spreader beams)

1. Aborted hole may be discarded provided it is not in direct line of the lifting load. If unsure, always fill aborted hole with high strength grout/mortar.
2. Mistake Plate shall be relocated 100mm to the left or right side from original position (maintaining the minimum edge distances) and redrill the holes.

Note 1: Where required all aborted holes must be filled with high strength grout/mortar.

Note 2: Where aborted holes are filled, the aged strength of grout/mortar shall be at least the strength of the concrete at time of lift.

Installation QA Check:

1. Anchor bolts should be verified at least weekly and after major weather events to ensure they are secure, in accordance with AS 3850.2:2024
2. Check if a bolt head can be turned by hand and if it turns, report it immediately to the responsible authority on site.
3. After installation of anchors with nominated assembly torque, put an alignment reference marks on the bolt head and the surrounding surface.
4. For BraceSet, using calibrated torque wrench, apply 100Nm torque in a clockwise direction.
5. If any anchor bolt turns more than 90° from the reference mark, then report this immediately to the responsible authority on site.



A - No Movement



B - Up to 45°



C - Up to 90°



D - Greater than 90°
Report to authority on site.

6. Total accumulated rotation of any bolt head should not exceed 180° from the first reference mark and if it does, report immediately to the responsible authority on site.
7. Reid™ does not recommend retorquing to the initial installation torque of 150Nm for BraceSet.

Quality and Compliance

AS 3850.1:2024
Compliant



All Reid™ branded products and all products manufactured at our Melbourne manufacturing facility are designed, manufactured, tested and supplied in compliance with our Quality Management System which has been independently audited and certified by SAI Global to ISO 9001:2015. Reid™ undertake strict quality control processes to ensure performance specifications and metallurgical properties are maintained.


To reflect the continued progress of the industry and the new innovative uses of precast and tilt-up construction, Australian Standard AS 3850 Part 1 and Part 2 has recently been updated in 2024. AS 3850 Part 1, Part 2 and Part 3 are detailed below.

- Part 1, called 'General requirements' details the updated performance and testing requirements for suppliers of componentry into the industry. These requirements are significantly different to AS 3850:2015 and should enable the industry to have greater confidence in the products that they are specifying and using.
- Part 2, called 'Building construction', aligns with the 2008 National Code of Practice for Precast, Tilt-Up and Concrete Elements in Building Construction and focuses on the interrelation of the various stages of manufacture, construction, transport and erection. It is specifically for the construction design and documentation of prefabricated concrete elements in building construction and provides guidance for the Erection Designer and highlights the importance of the Erection Design and Documentation. It was updated to align with the changes in Part 1 and the content in Part 3.
- Part 3, called 'Civil construction' provides requirements impacting prefabricated concrete elements in civil, infrastructure and non-building construction. Similar to Part 2, it focuses on various stages of safety, planning, manufacturing, construction design, casting, transportation, erection and incorporation into the final structure.

The new AS 3850.1:2024 is central for the safe, efficient and cost-effective manufacture, construction, transport and erection of prefabricated concrete elements.



Quality and compliance are at the core of everything we do. Our commitment to ISO 9001:2015 certification ensures every Reid™ product meets the highest standards of safety, performance, and reliability.





Customer Service

Reid™ Australia

Tel: 1300 780 250

Email: sales@itwcsanz.com

Web: www.reid.com.au

Reid™ New Zealand

Tel: 0800 88 22 12

Email: sales@ramsetreid.co.nz

Web: www.reids.co.nz

Reid™

AUS: 1 Ramset Drive, Chirside Park, Victoria, Australia, 3116

NZ: 23-29 Poland Road, Glenfield, Auckland 0632

Information in this document is correct at the time of printing. Readers should contact Reid or consult Reid detailed technical information to ensure product is suitable for intended use prior to purchase. ITW Australia Pty Ltd ABN 63 004 235 063 trading as Reid © copyright 2025™ Trademarks of Cetram Pty. Ltd. Used under license by Reid

Important Disclaimer: Any engineering information or advice ("Information") provided by Reid in this document is issued in accordance with a prescribed standard, published performance data or design software. It is the responsibility of the user to obtain its own independent engineering (or other) advice to assess the suitability of the Information for its own requirements. To the extent permitted by law, Reid will not be liable to the recipient or any third party for any direct or indirect loss or liability arising out of, or in connection with, the Information. None of the products listed in this document are subject to a warning or ban under the Building Act 2004.